Circular Wall Step Light



FIREFLY LIGHTING Phone: +61 7 3254 4333

Email: sales@fireflylighting.com.au

Address: 9/29 Links Ave North, Eagle Farm. Brisbane QLD 4009 Australia www.fireflylighting.com.au

LANDSCAPE RANGE COMMERCIAL GRADE

2W 24V 2700k






















Firefly Lighting's Range of Landscape products make light work of illuminating various outdoor environments. We created this range to sustain Australia's extreme weather conditions so the product lasts well beyond its warranty period and leaves our customers with a smile from ear to ear. All our landscape products are IP rated, and come standard with anti-glare honeycombs and bevel cut hoods. Simply connect into existing 24V DC transformers, and you're good to go!

SPECIFICATIONS

| SKU | LS-SL-BL-B | | |
|-----------------|-------------------------|--|--|
| Туре | Recessed Wall Luminaire | | |
| Lighting Output | 49lm | | |
| Wattage | 2W | | |
| Colour | Warm White | | |
| ССТ | 2700K | | |
| Beam Angle | 50° | | |
| Light Source | 1x2W OSRAM | | |
| Voltage | 24V DC | | |
| Current | 500MA | | |
| Dimmable | Yes | | |
| Housing | 12# Die-cast aluminium | | |
| Mounting Sleeve | ABS | | |
| IK Rating | IK10 | | |
| IP Rating | IP65 | | |



DIMENSIONS




LUMINAIRE



PHOTOMETRIC DATA

Wide Beam - 50°



| Illuminance at a Distance | | | | |
|---------------------------|--|--|---|--|
| Center Beam LUX | | Beam Width V H | | |
| 6.20 LUX | Λ | 1.6m | 2.0m | |
| 1.55 LUX | 71\ | 3.2m | 4.1m | |
| 0.69 LUX | $/ \square$ | 4.8m | 6.1m | |
| 0.39 LUX | | 6.4m | 8.1m | |
| 0.24 LUX | Т | 8.0m | 10.1m | |
| 0.17 LUX | | 9.6m | 12.2m | |
| | 6.20 LUX 1.55 LUX 0.69 LUX 0.39 LUX | 6.20 LUX 1.55 LUX 0.69 LUX 0.39 LUX 0.24 LUX | 6.20 LUX 1.6m 1.55 LUX 3.2m 0.69 LUX 4.8m 0.39 LUX 6.4m 0.24 LUX 8.0m | |